



- Intel® Celeron™ J1900 Quad Core 2,00 GHz
- 15.6" Projected Capacitive Multitouch Display (PCAP)
- Anodized Aluminum
- IP65 Front Protection
- Fanless compact design
- Made in Spain




CPU boards with latest generation Intel® Processors, fanless, low power consumption and exceptional performance.

IP65 Front Bezel protection, available in Anodized Aluminum or Stainless Steel.

5-Wire Resistive or Projected Capacitive Multitouch sensor (PCAP).



### Dimensions



### Specifications

#### Display

|                  |                                        |
|------------------|----------------------------------------|
| Touch technology | Projected Capacitive MultiTouch (PCAP) |
| Inches           | 15,6"                                  |
| Format           | 16:9                                   |
| Resolution       | 1920 x 1080                            |
| Backlight        | LED                                    |
| Brightness       | 450 cd/m2                              |
| Contrast Ratio   | 800:1                                  |
| Viewing Angle    | 160/160                                |
| LED Life Time    | 50.000 h                               |

#### System

|            |                                                                     |
|------------|---------------------------------------------------------------------|
| CPU        | Intel® Celeron® J1900 Quad Core 2,00 GHz                            |
| Memory     | 2Gb Scalable to 8Gb                                                 |
| Hard Drive | 60/120/240GB SSD. 500GB/1TB SATA.                                   |
| Graphics   | Intel® HD Graphics                                                  |
| Chipset    | J1900 Onboard (SoC)                                                 |
| OS         | Win7 Pro / Win7 Embedded / Win10 Pro / Win10 IoT Enterprise / Linux |

#### Input / Ouput

|              |                           |
|--------------|---------------------------|
| USB Ports    | 4 x USB 2.0               |
| Serial Ports | 1x RS-232/422/485         |
| Ethernet     | 2 x Realtek Giga Ethernet |
| Video        | 1 x VGA                   |
| Audio        | 1 x Audio output          |
| Expansión    | 2 x Mini-PCIe / 1 x PCIe1 |

#### Mechanical

|            |                    |
|------------|--------------------|
| Dimensions | 427 x 277 x 91 mm  |
| Weight     | 6,8 kg             |
| Mounting   | Frontal Wall-Mount |
| Panel cut  | 388 x 238 mm       |

#### Optionals

|              |                                              |
|--------------|----------------------------------------------|
| Screen       | High brightness for outdoors use             |
| USB Ports    | 2 x USB 2.0                                  |
| Serial Ports | 5 x RS-232                                   |
| Modem        | 3G / LTE + GPS                               |
| WIFI Module  | Wifi 2,4GHz / Wifi 2,4GHz i 5GHz + Bluetooth |
| Slot PCIe    | To Be Consulted                              |
| Others       | To Be Consulted                              |

#### Protection / Environmental Conditions

|                            |                                    |
|----------------------------|------------------------------------|
| IP & Material              | IP65 Anodized Aluminum Front Bezel |
| °C Operation               | 0° a 60° C / -20° a 60° C          |
| °C Storage                 | -10° a 70° C / -20° a 85° C        |
| Humidity (no condensation) | 0% a 95%                           |

#### Power Supply

|                        |                                                |
|------------------------|------------------------------------------------|
| Input Voltage          | 12Vdc (External power supply 110-220Vac/12Vdc) |
| Optional Input Voltage | 24Vdc                                          |