



- Intel® Core™ i3-7100U 2,40 GHz
- 21.5" 5-Wire Resistive Touch Screen
- Stainless Steel 316L
- IP65 Full Enclosure
- Fanless compact design
- Made in Spain



Intel®
Processors



Touch
Technology



Efficient Power
Consumption



Double
Display



IP65 Full
Enclosure


CPU boards with latest generation Intel® Processors, fanless, low power consumption and exceptional performance.

Manufactured in 316L Stainless Steel with full IP65 enclosure. Selection and configuration up to five ports, among COM (serial), USB or Ethernet ports, through IP68 connectors.

5-Wire Resistive or Projected Capacitive Multitouch sensor (PCAP).



Dimensions



Specifications

Display	
Touch technology	5 Wire Resistive
Inches	21,5"
Format	16:9
Resolution	1920 x 1080
Backlight	LED
Brightness	300 cd/m2
Contrast Ratio	5000:1
Viewing Angle	178/178
LED Life Time	50.000 h

System	
CPU	Intel® Core™ i3-7100U (7th Generation) 2,40 GHz
Memory	DDR4 2Gb Scalable to 16Gb
Hard Drive	60/120/240GB SSD. 500GB/1TB SATA.
Graphics	Intel® HD Graphics 620
Chipset	i3-7100U Onboard (SoC)
OS	Win7 Pro / Win7 Embedded / Win10 Pro / Win10 IoT Enterprise / Linux

Input / Output	
USB Ports	2 x USB 3.0
Serial Ports	-
Ethernet	2 x Realtek Giga Ethernet
Video	1 x VGA / 1 x HDMI
Audio	1 x Audio output / 1 x Microphone
Expansión	1 x Mini-PCle / 1 x M.2(2242/2260) for SSD

Mechanical	
Dimensions	591 x 406 x 79 mm
Weight	14,5 kg
Mounting	VESA 100 x 100, Wall, Bracket, Holder
Panel cut	-

Optionals	
USB Ports	3 x USB 2.0 / 2 x USB 3.0
Serial Ports	2 x RS-232 selectable header 5V-12V / 10 x RS-232/422/485
Modem	3G / LTE + GPS
WIFI Module	Wifi 2,4GHz / Wifi 2,4GHz i 5GHz + Bluetooth
Slot PCIe	To Be Consulted
Others	To Be Consulted

Protection / Environmental Conditions	
IP & Material	Full IP65 Stainless Steel 316L
°C Operation	0° a 60° C / -20° a 60° C
°C Storage	-10° a 70° C / -20° a 85° C
Humidity (no condensation)	0% a 95%

Power Supply	
Input Voltage	12Vdc (External power supply 110-220Vac/12Vdc)
Optional Input Voltage	24Vdc